

# **Safety Data Sheet**

LOCTITE EA E-30 CL RESIN

Page 1 of 8

SDS No.: 157210

V001.1

Revision: 12.04.2021 printing date: 26.05.2025

## SECTION 1 IDENTIFICATION OF THE MATERIAL AND SUPPLIER

**Product name:** LOCTITE EA E-30 CL RESIN

Intended use: Epoxy resin

Supplier:

Henkel New Zealand Ltd

2 Allens Rd Auckland, 2013 New Zealand

Phone: +64 (9) 272-6710

**Emergency information:** 24 HOUR EMERGENCY CONTACT NUMBER 0800 243 622

## **SECTION 2 HAZARDS IDENTIFICATION**

## Classification of the substance or mixture

Classified as hazardous under the New Zealand Hazardous Substances and New Organisms Act (HSNO).

### **GHS Classification:**

Hazard ClassHazard CategorySkin irritationCategory 2Serious eye irritationCategory 2ASkin sensitizerCategory 1Acute hazards to the aquaticCategory 2environmentCategory 2

Chronic hazards to the aquatic

environment

Category 2

Hazard pictogram:



Signal word: Warning

V001.1 LOCTITE EA E-30 CL RESIN

**Hazard statement(s):** H315 Causes skin irritation.

H317 May cause an allergic skin reaction. H319 Causes serious eye irritation.

H411 Toxic to aquatic life with long lasting effects.

**Precautionary Statement(s):** 

**Prevention:** P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P264 Wash hands thoroughly after handling.

P272 Contaminated work clothing should not be allowed out of the workplace.

P273 Avoid release to the environment. P280 Wear eye protection/face protection.

P280 Wear protective gloves.

**Response:** P302+P352 IF ON SKIN: Wash with plenty of water.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing.

P333+P313 If skin irritation or rash occurs: Get medical advice/attention. P337+P313 If eye irritation persists: Get medical advice/attention.

P362 Take off contaminated clothing.

P391 Collect spillage.

**Disposal:** P501 Dispose of contents/container to an appropriate treatment and disposal facility in

accordance with applicable laws and regulations.

## SECTION 3 COMPOSITION/INFORMATION ON INGREDIENTS

**General chemical description:** Mixture

resins

**Type of preparation:** Epoxy Adhesive

 ${\bf Identity\ of\ ingredients:}$ 

Chemical ingredients	CAS-No.	Proportion
reaction product: bisphenol-A-(epichlorhydrin)	25068-38-6	60- < 100 %
2,2'-[methylenebis(p-	2095-03-6	< 1 %
phenyleneoxymethylene)]bisoxirane		
non hazardous ingredients~		1- < 3 %

## SECTION 4 FIRST AID MEASURES

**Ingestion:** Do not induce vomiting.

Have victim rinse mouth thoroughly with water.

Seek medical advice.

**Skin:** Remove contaminated clothing and footwear.

Immediately flush skin with plenty of water (using soap, if available).

Seek medical advice.

Eyes: Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.

Seek medical advice.

**Inhalation:** Move to fresh air.

Keep warm and in a quiet place.

If adverse health effects develop seek medical attention.

First Aid facilities: Eye wash and safety shower

Normal washroom facilities

Medical attention and special

treatment:

Treat symptomatically and supportively.

### SDS No.: 157210 LOCTITE EA E-30 CL RESIN

V001.1

### **SECTION 5. FIRE FIGHTING MEASURES**

Suitable extinguishing media: Water spray (fog), foam, dry chemical or carbon dioxide.

Decomposition products in case of

Thermal decomposition can lead to release of irritating gases and vapors.

fire:

Carbon monoxide. Carbon dioxide

Irritating organic fragments.

Aldehydes. Acids.

Oxides of nitrogen.

Particular danger in case of fire:

Closed containers may rupture (due to build up of pressure) when exposed to extreme

Special protective equipment for

fire-fighters:

Wear protective equipment.

Fire fighters should wear positive pressure self-contained breathing apparatus (SCBA).

Additional fire fighting advice: In case of fire, keep containers cool with water spray.

Collect contaminated fire fighting water separately. It must not enter drains.

## SECTION 6. ACCIDENTAL RELEASE MEASURES

**Personal precautions:** Ensure adequate ventilation.

> Avoid contact with skin and eyes. Wear protective equipment.

**Environmental precautions:** Do not allow product to enter sewer or waterways.

Clean-up methods: Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder,

sawdust).

Scrape up as much material as possible. Clean residue with soap and water.

Store in a closed container until ready for disposal.

#### HANDLING AND STORAGE **SECTION 7.**

Precautions for safe handling: Use only with adequate ventilation.

Prevent contact with eyes, skin and clothing. Do not breathe vapor and mist. Wash

thoroughly after handling. Keep container closed.

Wear suitable protective clothing, safety glasses and gloves.

Store in original containers at 8-21°C (46.4-69.8°F) and do not return residual materials to Conditions for safe storage:

containers as contamination may reduce the shelf life of the bulk product.

Keep container tightly sealed.

Keep container in a well ventilated place.

#### **SECTION 8. EXPOSURE CONTROLS / PERSONAL PROTECTION**

Workplace exposure standards:

None

**Biological Exposure Indices:** 

None

Page 4 of 8 LOCTITE EA E-30 CL RESIN V001.1

**Engineering controls:** Use local exhaust ventilation if the potential for airborne exposure exists.

Eye protection: Wear protective glasses with side-pieces.

Skin protection: Use chemical resistant, impermeable clothing including gloves and either an apron or

body suit to prevent skin contact.

**Respiratory protection:** If inhalation risk exists, wear a respirator or air supplied mask complying with the

requirements of AS/NZS 1715 and AS/NZS 1716.

## SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance: Clear, Colorless to light yellow

Liquid

Faint Odor:

Flash point: > 93 °C (> 199.4 °F)

Estimated

Density: 1.1 g/cm3

Solubility in water: Not miscible or difficult to mix

**VOC** content: < 1 % < 10 g/l

#### **SECTION 10.** STABILITY AND REACTIVITY

Stability: Stable under normal conditions of temperature and pressure.

Conditions to avoid: Heat, flames, sparks and other sources of ignition.

**Incompatible materials:** Strong acids and strong bases.

Strong oxidizing agents. Avoid contact with amines.

Hazardous decomposition

products:

Thermal decomposition can lead to release of irritating gases and vapors.

carbon monoxide Carbon dioxide. Aldehydes.

Irritating organic vapours.

Acids.

Oxides of nitrogen.

Hazardous polymerization: Reaction with some curing agents may produce an exothermic reaction which in large

masses could cause runaway polymerization.

## SECTION 11 TOXICOLOGICAL INFORMATION

## SDS No.: 157210 V001.1

## LOCTITE EA E-30 CL RESIN

**Health Effects:** 

**Ingestion:** May cause gastrointestinal disturbances such as nausea, vomiting, abdominal pain, and diarrhea.

**Skin:** Causes skin irritation.

Symptoms may include redness, edema, drying, defatting and cracking of the skin.

May cause skin sensitization.

Eyes: Causes serious eye irritation.

This product may cause irritation with stinging, tearing, and redness.

**Inhalation:** Inhalation of mists/vapors of this product may cause dizziness, nausea, and respiratory tract

congestion.

### Acute toxicity:

Hazardous components	Value	Value	Route of	Exposure	Species	Method
CAS-No.	type		application	time		
reaction product:	LD50	> 2,000 mg/kg	oral		rat	OECD Guideline 420 (Acute
bisphenol-A-	LD50	> 2,000 mg/kg			rat	Oral Toxicity)
(epichlorhydrin)			dermal			OECD Guideline 402 (Acute
25068-38-6						Dermal Toxicity)
2,2'-[methylenebis(p-	LD50	> 2,000 mg/kg	oral		rat	OECD Guideline 420 (Acute
phenyleneoxymethylene)]	LD50	> 2,000 mg/kg			rat	Oral Toxicity)
bisoxirane			dermal			OECD Guideline 402 (Acute
2095-03-6						Dermal Toxicity)

### Skin corrosion/irritation:

Hazardous components	Result	Exposure	Species	Method
CAS-No.		time		
reaction product: bisphenol-A- (epichlorhydrin) 25068-38-6	not irritating	4 h	rabbit	not specified

### Serious eye damage/irritation:

Hazardous components CAS-No.	Result	Exposure time	Species	Method
reaction product:	not irritating		rabbit	OECD Guideline 405 (Acute
bisphenol-A-				Eye Irritation / Corrosion)
(epichlorhydrin)				
25068-38-6				

## Respiratory or skin sensitization:

Hazardous components CAS-No.	Result	Test type	Species	Method
reaction product: bisphenol-A- (epichlorhydrin) 25068-38-6	sensitising	Mouse local lymphnod e assay (LLNA)	mouse	OECD Guideline 429 (Skin Sensitisation: Local Lymph Node Assay)
2,2'-[methylenebis(p- phenyleneoxymethylene)] bisoxirane 2095-03-6	sensitising	Mouse local lymphnod e assay (LLNA)	mouse	OECD Guideline 429 (Skin Sensitisation: Local Lymph Node Assay)

## Germ cell mutagenicity:

Hazardous components CAS-No.	Result	Type of study / Route of administration	Metabolic activation / Exposure time	Species	Method
reaction product: bisphenol-A- (epichlorhydrin) 25068-38-6	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		OECD Guideline 472 (Genetic Toxicology: Escherichia coli, Reverse Mutation Assay)
reaction product: bisphenol-A- (epichlorhydrin) 25068-38-6	negative	oral: gavage		mouse	not specified

Page 6 of 8

SDS No.: 157210 V001.1

## LOCTITE EA E-30 CL RESIN

## Repeated dose toxicity:

Hazardous components CAS-No.	Result	Route of application	Exposure time / Frequency of treatment	Species	Method
reaction product:	NOAEL=50 mg/kg	oral: gavage	14 wdaily	rat	OECD Guideline 408
bisphenol-A-					(Repeated Dose 90-Day Oral
(epichlorhydrin)					Toxicity in Rodents)
25068-38-6					

# SECTION 12. ECOLOGICAL INFORMATION

**General ecological information:** Do not empty into drains / surface water / ground water.

**Ecotoxicity:** Toxic to aquatic life with long lasting effects.

## **Toxicity:**

Hazardous components	Value	Value	Acute	Exposure	Species	Method
CAS-No.	type		Toxicity Study	time		
reaction product: bisphenol-A-	LC50	1.75 mg/l	Fish	96 h	Oncorhynchus mykiss	OECD Guideline
(epichlorhydrin)						203 (Fish, Acute
25068-38-6	EC50	1.7 ma/l	Domhnio	48 h	Donhuio magno	Toxicity Test) OECD Guideline
reaction product: bisphenol-A- (epichlorhydrin)	ECSU	1.7 mg/l	Daphnia	48 N	Daphnia magna	202 (Daphnia sp.
25068-38-6						Acute
25000 50 0						Immobilisation
						Test)
reaction product: bisphenol-A-	EC50	> 11 mg/l	Algae	72 h	Scenedesmus capricornutum	OECD Guideline
(epichlorhydrin)						201 (Alga, Growth
25068-38-6	NOEC	4.2 //	A.1	72 h	C	Inhibition Test) OECD Guideline
reaction product: bisphenol-A- (epichlorhydrin)	NOEC	4.2 mg/l	Algae	/ Z II	Scenedesmus capricornutum	201 (Alga, Growth
25068-38-6						Inhibition Test)
reaction product: bisphenol-A-	IC50	> 100 mg/l	Bacteria	3 h	activated sludge, industrial	other guideline:
(epichlorhydrin)		-			_	
25068-38-6						
2,2'-[methylenebis(p-	LC50	> 1 - 10 mg/l	Fish	96 h	not specified	OECD Guideline
phenyleneoxymethylene)]biso xirane						203 (Fish, Acute Toxicity Test)
2095-03-6						Toxicity Test)
2,2'-[methylenebis(p-	EC50	> 1 - 10 mg/l	Daphnia	48 h	Daphnia magna	OECD Guideline
phenyleneoxymethylene)]biso			-		•	202 (Daphnia sp.
xirane						Acute
2095-03-6						Immobilisation
1						Test)

## Persistence and degradability:

Hazardous components	Result	Route of	Degradability	Method
CAS-No.		application		
reaction product: bisphenol-A-	not readily biodegradable.	aerobic	5 %	OECD Guideline 301 F (Ready
(epichlorhydrin)				Biodegradability: Manometric
25068-38-6				Respirometry Test)
2,2'-[methylenebis(p-	not readily biodegradable.	aerobic	< 10 %	OECD 301 A - F
phenyleneoxymethylene)]biso				
xirane				
2095-03-6				

## Bioaccumulative potential / Mobility in soil:

Hazardous components	LogPow	Bioconcentration	Exposure	Species	Temperature	Method
CAS-No.		factor (BCF)	time			
reaction product: bisphenol-A-	3.242				25 °C	EU Method A.8 (Partition Coefficient)
(epichlorhydrin) 25068-38-6						Coefficient)

V001.1

#### **SECTION 13. DISPOSAL CONSIDERATIONS**

Waste disposal of product: Dispose of in accordance with local and national regulations.

Disposal for uncleaned package: After use, tubes, cartons and bottles containing residual product should be disposed of as

chemically contaminated waste in an authorised legal land fill site or incinerated.

#### **SECTION 14** TRANSPORT INFORMATION

**Land Transport:** 

UN no.:

Proper shipping name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID,

N.O.S. (Bisphenol-A Epichlorhydrin resin)

Class or division: Packing group: Ш

**Marine transport IMDG:** 

3082 UN no .:

ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, Proper shipping name:

N.O.S. (Bisphenol-A Epichlorhydrin resin)

Class or division: Packing group: Ш F-A .S-F EmS: Seawater pollutant: Marine pollutant

Air transport IATA:

UN no .: 3082

Proper shipping name: Environmentally hazardous substance, liquid, n.o.s. (Bisphenol-A

Epichlorhydrin resin)

Class or division: Ш Packing group: Packing instructions (passenger) 964 Packing instructions (cargo) 964

### **Further information for transport:**

The transport classifications in this section apply generally to packed and bulk goods alike. For containers with a net volume of no more than 5 L for liquid substances or a net mass of no more than 5 kg for solid substances per individual or inner package, the exemptions SP 375 (ADR), 197 (IATA), 969 (IMDG) may be applied, which can result in a deviation from the transport classification for packed goods.

#### REGULATORY INFORMATION SECTION 15.

## New Zealand regulatory information:

Classified as hazardous under the New Zealand Hazardous Substances and New Organisms Act (HSNO).

**HSNO Approval Number:** Group standard HSR002658

NZIoC: Compliant for NZIOC

#### **SECTION 16.** OTHER INFORMATION

Abbreviations/acronyms: HSNO - Hazardous Substances and New Organisms

IMDG: International Maritime Dangerous Goods code

IATA-DGR: International Air Transport Association - Dangerous Goods Regulations

SDS No.: 157210

Page 8 of 8

## LOCTITE EA E-30 CL RESIN

V001.1

**Reason for issue:** Reviewed SDS. Reissued with new date. involved chapters:

**Date of previous issue:** 07.08.2016

Disclaimer:

The percentage weight (% w/w) of ingredients is not to be taken as a specification guaranteed by Henkel New Zealand Limited, but only as an approximate guide to the content of hazardous ingredients in the material. The information contained herein does not constitute a guarantee by Henkel New Zealand Limited concerning the properties of the material.

The information contained in this Safety Data Sheet is offered in good faith and has been developed from what is believed to be accurate and reliable sources. The information is offered without warranty, representation, inducement or licence and Henkel New Zealand Limited assumes no legal responsibility for reliance upon same. Henkel New Zealand Limited disclaims any liability for loss, injury or damage incurred in connection with the use of the material or its associated Safety Data Sheet.

This information is not to be construed as a representation that the material is suitable for any particular purpose or use except those conditions and warranties implied by Government statutes. Customers are encouraged to make their own enquiries as to the material's characteristics and, where appropriate, to conduct their own tests in the specific context of the material's intended use.

No warranty or representation of any kind is given with respect to the substantive or export laws of any other jurisdiction or country. Please confirm that the information provided herein conforms to the substantive export or other law of any other jurisdiction prior to export. Please contact Henkel Product Safety and Regulatory Affairs for additional assistance.