



Epoxy Pigment Paste

Introduction:

Adhesive Technologies Epoxy Pigment Paste is a highly filled, solvent free pigment paste specifically formulated for the use with the ATL epoxy range of resin and hardeners to cure at room temperature or low temperature applications in fibre composite boat construction.

High pigment loading makes this an easy to use pigment dispersion suitable for gelcoats and coating applications.

Typical Applications:

- ❖ Tinting
- ❖ Gelcoats
- ❖ Coatings

Mix Ratio:

Recommend Loadings: Up to 5% by weight. Loadings higher than 5% may be used; however please contact manufacturer prior to use.

Note: Care should be taken when dispensing and mixing.
Optimum results are achieved when recommended ratios are used.

Uncured Properties:

Physical State Black, White

Specific Gravity (g/ml) 2.00

Storage:

Epoxy Pigment Paste will keep for 2 years if kept in original containers at room temperature (15°C – 32°C) and out of direct sunlight. Containers should be tightly sealed to prevent moisture absorption. Some settling may occur during storage, mix thoroughly before use if necessary.

Note: Our products are intended for sale to industrial and commercial customers. We request that customers inspect and test our products before use and satisfy themselves as to contents and suitability. Nothing herein shall constitute a warranty, express or implied, including any warranty or merchantability or fitness, nor is protection from law or patent to be inferred. All patent rights are reserved. The exclusive remedy for all proven claims is replacement of our materials and in no event shall we be liable for special or consequential damages.



adhesivetech

17 Corban Avenue, Henderson, Waitakere 0612
P.O. Box 21169, Henderson, Waitakere 0650, Auckland, New Zealand
Phone: +64 9 838 6961 Website: adhesivetech.co.nz

VERSION: 1.0

DATE ISSUED: 10/01/2024

Epoxy Pigment Paste

Health & Safety:

Adhesive Technologies NZ Ltd provides its customers with a product specific Material Safety Data Sheet (MSDS) to cover potential health effects, safe handling, storage, use and disposal information.

- ❖ Use with good ventilation and adequate safety equipment including gloves.
- ❖ If skin contact occurs, wash with lanolin based hand-cleaner and water.
- ❖ If eye contact occurs, immediately wash for 15 minutes with running water.
- ❖ If swallowed:

Resins - DO NOT induce vomiting, and contact a doctor or the Poisons Information Centre.

Hardeners – DO NOT induce vomiting, give plenty of milk or water and contact a doctor or Poisons Information Centre.

Note: Our products are intended for sale to industrial and commercial customers. We request that customers inspect and test our products before use and satisfy themselves as to contents and suitability. Nothing herein shall constitute a warranty, express or implied, including any warranty or merchantability or fitness, nor is protection from law or patent to be inferred. All patent rights are reserved. The exclusive remedy for all proven claims is replacement of our materials and in no event shall we be liable for special or consequential damages.