

MATERIAL SAFETY DATA SHEET

Issue date: DECEMBER 2017

1. IDENTIFICATION OF THE PRODUCT AND THE COMPANY

Product Name: WOODLOK 3600 Polyurethane Glue

Supplier: GLUE GURU
Address: 18 Kaimahi Road
Wairau Valley
Auckland 0627
New Zealand

Telephone (09) 444 4878 Customer Services

Fax (09) 442 5975

Emergency Telephone + 64 274 736008 (24 hours)
National Poison Centre (24 hours): 0800 POISON [764 766]

2. HAZARDS IDENTIFICATION

Irritating to eyes, respiratory system and skin.
Toxic Substance: Not classified

3. COMPOSITION/INFORMATION ON INGREDIENTS

Product Description	Adhesive	
Polymeric MDI	9016-87-9	30-60%
4,4-diphenylmethane diisocyanate	101-68-8	30-60%
MDI Mixed Isomers	26447-40-5	<1%

4. FIRST AID MEASURES

If poisoning occurs, contact a doctor or Poisons Information Centre Phone 0800 764 766.

Ingestion: Immediately rinse mouth with water. Do not induce vomiting. Seek medical assistance.

Inhalation: Remove victim from area of exposure. Remove contaminated clothing and loosen remaining clothing. If breathing is difficult seek immediate medical attention.

MATERIAL SAFETY DATA SHEET (MSDS)

WOODLOK 3600 Polyurethane Glue



Skin Contact: Wash contaminated skin with plenty of soap and water. Remove contaminated clothing and wash before re-use. Seek medical advice if necessary.

Eye Contact: Immediately irrigate with copious quantities of water for at least 15 minutes. Eyelids to be held open. Seek immediate medical assistance.

Notes to physician: The manifestations of respiratory symptoms including pulmonary edema, resulting from acute exposure may be delayed. Supportive care. Treatment based on judgment by the doctor in response to reactions of the patient.

5. FIRE-FIGHTING MEASURES

Specific Hazards: Will support combustion. Toxic fumes are released in fire situations.

Fire-fighting advice: On burning may emit toxic fumes including those of carbon monoxide, nitrogen oxide, isocyanate vapours and hydrogen cyanide. Fire fighters to wear self-contained breathing apparatus and suitable protective clothing if risk of exposure to vapour or products of combustion.

Suitable Extinguishing Media: Dry chemical powder, Carbon dioxide, chemical foam; in case of larger fires, water spray should be used.

6. ACCIDENTAL RELEASE MEASURES

Evacuate spill area. Contain spill. Wear protective clothing and breathing apparatus during clean up. Absorb spill with sand or earth and shovel into open top containers, do not make pressure tight. Treat with neutralizing solution (90% water, 2-7% detergent, 3-8% concentrated ammonium hydroxide). About 10 parts neutralizing solution per part of isocyanate with mixing.

7. HANDLING AND STORAGE

Handling advice: Avoid skin and eye contact.

Storage advice: Store in a cool place and out of direct sunlight. Store away from alcohols, amines, moisture and sources of heat or ignition. Keep dry, reacts with water. Keep containers closed at all times, check regularly for leaks.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Occupational Exposure Limits:

No value assigned for this specific material by the New Zealand Occupational Safety and Health Service (OSH). However, Workplace Exposure Standard(s) for constituent(s):

DEC 2017

MATERIAL SAFETY DATA SHEET (MSDS)

WOODLOK 3600 Polyurethane Glue



Isocyanates, all (as-NCO): TWA 0.02 mg/m³; STEL 0.07 mg/m³, sen, NZ
As published by the New Zealand Occupational Safety and Health Service (OSH)

'Sen' Notice – sensitiser. The substance can cause a specific immune response in some people. An affected individual may subsequently react to exposure to minute levels of that substance.

These Exposure Standards are guides to be used in the control of occupational health hazards. All atmospheric contamination should be kept to as low a level as is workable. These exposure standards should not be used as fine dividing lines between safe and dangerous concentrations of chemicals. They are not a measure of relative toxicity.

Engineering Control Measures:

Ensure ventilation is adequate and that air concentrations of components are controlled below quoted Exposure Standards. Use in well-ventilated area. Keep containers closed when not in use.

Personal Protective Equipment:

Avoid skin and eye contact and inhalation of vapour or spray. Wear overalls, safety boots, full-face visor and general purpose gloves (PVC). Use with adequate ventilation. If inhalation risk exists wear organic vapour/particulate respirator meeting the requirements of AS/NZS 1715 and AS/NZS 1716. Always wash hands before smoking, eating, drinking or using the toilet. Wash contaminated clothing and other protective equipment before storage or re-use.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	Brown liquid
Solubility	Insoluble in water
Specific Gravity	1.1
Flash Point (°C)	>100°C
Flammability Limits (%)	Not applicable
Boiling Point / Range (°C)	180

10. STABILITY AND REACTIVITY

Stability Reacts with alcohols, amines and moisture.

11. TOXICOLOGICAL INFORMATION

No adverse health effects expected if the product is handled in accordance with this Safety Data Sheet and the product label. Symptoms or effects that may arise if the product is mishandled and overexposure occurs are:

Ingestion: May cause vomiting, nausea and abdominal pain.

Eye contact: May cause slight eye irritation.

MATERIAL SAFETY DATA SHEET (MSDS)

WOODLOK 3600 Polyurethane Glue



Skin contact: Prolonged or repeated exposure may cause skin irritation. May result in allergic skin reactions or respiratory sensitization.

Inhalation: Vapours may cause irritation of the mucous membranes in the throat and lungs. May cause respiratory sensitization in susceptible individuals. MDI concentrations below the exposure standard may cause allergic respiratory reactions in individuals already sensitized. Symptoms may include coughing, difficult breathing and a feeling of tightness in the chest. Effects may be delayed.

Long Term Effects:

There are reports that chronic exposure to isocyanates by inhalation, may result in a permanent decrease in lung function.

Toxicological Data:

No LD50 data available for the product. The toxicity of the product may be attributed to the solvents it contains.

However, for constituent MDI products:

Oral LD50 (rat): >10000 mg/kg

Dermal LD50 (rabbit): >9400 mg/kg

Inhalation LC50 (rat): 490 mg/m³/4h

12. ECOLOGICAL INFORMATION

Avoid contaminating waterways, drains, sewers or ground. LC50>100 mg/l in most sensitive species.

13. DISPOSAL CONSIDERATIONS

Refer to Waste Management Authority. Dispose of material through a licensed waste contractor. Should be incinerated in a hazardous waste incinerator in accordance with relevant regulations.

14. TRANSPORT INFORMATION

Not classified as Dangerous Goods by NZS 5433:1999 Transport of Dangerous Goods on Land.

Marine Transport

Not classified as Dangerous Goods by the criteria of the International Maritime Dangerous Goods Code (IMDG Code) for transport by sea.

Air Transport

Not classified as Dangerous Goods by the criteria of the International Air Transport Association (IATA) Dangerous Goods Regulations for transport by air.

15. REGULATORY INFORMATION

Not classified as hazardous.

16. OTHER INFORMATION

New Zealand National Poison Information Centre (24 hours): 0800 POISON [764 766]
New Zealand Emergency Services: 111

WHILST THE INFORMATION CONTAINED IN THIS DOCUMENT IS BASED ON DATA WHICH, TO THE BEST OF OUR KNOWLEDGE, WAS ACCURATE AND RELIABLE AT THE TIME OF PREPARATION, NO RESPONSIBILITY CAN BE ACCEPTED BY US FOR ERRORS AND OMISSIONS. THE PROVISION OF THIS INFORMATION SHOULD NOT BE CONSTRUED AS A RECOMMENDATION TO USE ANY OF OUR PRODUCTS IN VIOLATION OF ANY PATENT RIGHTS OR IN BREACH OF ANY STATUTE OR REGULATION. USERS ARE ADVISED TO MAKE THEIR OWN DETERMINATION AS TO THE SUITABILITY OF THIS INFORMATION IN RELATION TO THEIR PARTICULAR PURPOSE AND SPECIFIC CIRCUMSTANCES. SINCE THE INFORMATION CONTAINED IN THIS DOCUMENT MAY BE APPLIED UNDER CONDITIONS BEYOND OUR CONTROL, NO RESPONSIBILITY CAN BE ACCEPTED BY US FOR ANY LOSS OR DAMAGE CAUSED BY ANY PERSON ACTING OR REFRAINING FROM ACTION AS A RESULT OF THIS INFORMATION.

End of Safety Data Sheet.