

# SAFETY DATA SHEET

## SikaBond® T55



Version 1.0

MSDS Number: 000000601639

Revision Date: 2015/12/08

### SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Product name : SikaBond® T55  
Product code : 000000601639  
Type of product : liquid

#### Manufacturer or supplier's details


Company : Sika (NZ) Ltd.  
85-91 Patiki Road  
Avondale  
Auckland AKL 1026  
Telephone : +64 9 820 2900  
Emergency telephone number : 0800 734 607  
Telefax : +64 9 828 4091  
E-mail address : info@nz.sika.com

### SECTION 2. HAZARDS IDENTIFICATION

#### GHS Classification

Flammable Liquids : Category C  
Skin irritation : Category B  
Eye irritation : Category A  
Respiratory sensitisation : Category A  
Skin sensitisation : Category B  
Carcinogenicity : Category B  
Toxic to Reproduction : Category B  
Specific Target Organ Toxicity (Oral) : Category B  
Specific Target Organ Toxicity (Inhalation) : Category B

#### GHS Label element

Hazard pictograms : 

Signal word : Danger

# SAFETY DATA SHEET

## SikaBond® T55



Version 1.0

MSDS Number: 00000601639

Revision Date: 2015/12/08

- Hazard statements : H226 Flammable liquid and vapour.  
H316 Causes mild skin irritation.  
H317 May cause an allergic skin reaction.  
H319 Causes serious eye irritation.  
H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.  
H351 Suspected of causing cancer.  
H361 Suspected of damaging fertility or the unborn child.  
H371 May cause damage to organs if swallowed.  
H371 May cause damage to organs if inhaled.
- Precautionary statements : **Prevention:**  
P201 Obtain special instructions before use.  
P202 Do not handle until all safety precautions have been read and understood.  
P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.  
P233 Keep container tightly closed.  
P240 Ground/bond container and receiving equipment.  
P241 Use explosion-proof electrical/ ventilating/ lighting/ equipment.  
P242 Use only non-sparking tools.  
P243 Take precautionary measures against static discharge.  
P260 Do not breathe dust/ fume/ gas/ mist/ vapours/ spray.  
P264 Wash skin thoroughly after handling.  
P270 Do not eat, drink or smoke when using this product.  
P272 Contaminated work clothing should not be allowed out of the workplace.  
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.  
**Response:**  
P303 + P361 + P353 IF ON SKIN (or hair): Remove/ Take off immediately all contaminated clothing. Rinse skin with water/ shower.  
P304 + P341 IF INHALED: If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing.  
P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P308 + P313 IF exposed or concerned: Get medical advice/ attention.  
P309 + P311 IF exposed or if you feel unwell: Call a POISON CENTER or doctor/ physician.  
P321 Specific treatment (see supplemental first aid instructions on this label).  
P333 + P313 If skin irritation or rash occurs: Get medical advice/ attention.  
P337 + P313 If eye irritation persists: Get medical advice/ attention.  
P363 Wash contaminated clothing before reuse.  
P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam for extinction.  
**Storage:**  
P403 + P235 Store in a well-ventilated place. Keep cool.  
P405 Store locked up.

# SAFETY DATA SHEET

## SikaBond® T55



Version 1.0

MSDS Number: 000000601639

Revision Date: 2015/12/08

### Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

### Other hazards which do not result in classification

None known.

## SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

### Hazardous components

Chemical Name	CAS-No.	Concentration (%)
Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)	64742-82-1	>= 1 - < 10
xylene	1330-20-7	>= 1 - < 10
aromatic polyisocyanate	53317-61-6	>= 0.1 - < 1
ethylbenzene	100-41-4	>= 0.1 - < 1
4,4'-methylenediphenyl diisocyanate	101-68-8	>= 0.1 - < 1

## SECTION 4. FIRST AID MEASURES

- General advice : Move out of dangerous area.  
Consult a physician.  
Show this safety data sheet to the doctor in attendance.
- If inhaled : Move to fresh air.  
Consult a physician after significant exposure.
- In case of skin contact : Take off contaminated clothing and shoes immediately.  
Wash off with soap and plenty of water.  
If symptoms persist, call a physician.
- In case of eye contact : Remove contact lenses.  
Keep eye wide open while rinsing.  
If eye irritation persists, consult a specialist.
- If swallowed : Clean mouth with water and drink afterwards plenty of water.  
Do not give milk or alcoholic beverages.  
Never give anything by mouth to an unconscious person.
- Most important symptoms and effects, both acute and delayed : No known significant effects or hazards.  
See Section 11 for more detailed information on health effects and symptoms.  
Causes mild skin irritation.  
May cause an allergic skin reaction.  
Causes serious eye irritation.  
May cause allergy or asthma symptoms or breathing difficulties if inhaled.  
Suspected of causing cancer.  
Suspected of damaging fertility or the unborn child.  
May cause damage to organs if swallowed.  
May cause damage to organs if inhaled.

# SAFETY DATA SHEET

## SikaBond® T55



Version 1.0

MSDS Number: 000000601639

Revision Date: 2015/12/08

Notes to physician : Treat symptomatically.

---

### SECTION 5. FIREFIGHTING MEASURES

- Suitable extinguishing media : Alcohol-resistant foam  
Carbon dioxide (CO<sub>2</sub>)  
Dry chemical
- Unsuitable extinguishing media : Water  
High volume water jet
- Specific hazards during fire-fighting : Do not use a solid water stream as it may scatter and spread fire.
- Hazardous combustion products : No hazardous combustion products are known
- Specific extinguishing methods : Use water spray to cool unopened containers.
- Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.

---

### SECTION 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.  
Remove all sources of ignition.  
Deny access to unprotected persons.
- Environmental precautions : Prevent product from entering drains.  
If the product contaminates rivers and lakes or drains inform respective authorities.

---

### SECTION 7. HANDLING AND STORAGE

- Advice on protection against fire and explosion : Use explosion-proof equipment. Keep away from heat/sparks/open flames/hot surfaces. No smoking. Take precautionary measures against electrostatic discharges.
- Advice on safe handling : Do not breathe vapours or spray mist.  
Avoid exceeding the given occupational exposure limits (see section 8).  
Do not get in eyes, on skin, or on clothing.  
For personal protection see section 8.  
Smoking, eating and drinking should be prohibited in the application area.  
Take precautionary measures against static discharge.  
Open drum carefully as content may be under pressure.  
Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours).  
Follow standard hygiene measures when handling chemical products

# SAFETY DATA SHEET

## SikaBond® T55



Version 1.0

MSDS Number: 00000601639

Revision Date: 2015/12/08

- Hygiene measures : Handle in accordance with good industrial hygiene and safety practice.  
When using do not eat or drink.  
When using do not smoke.  
Wash hands before breaks and at the end of workday.
- Conditions for safe storage : Store in original container.  
Keep in a well-ventilated place.  
Observe label precautions.  
Store in accordance with local regulations.

### SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
xylene	1330-20-7	WES-TWA	50 ppm 217 mg/m <sup>3</sup>	NZ OEL
		TWA	100 ppm	ACGIH
		STEL	150 ppm	ACGIH
ethylbenzene	100-41-4	WES-STEL	125 ppm 543 mg/m <sup>3</sup>	NZ OEL
		WES-TWA	100 ppm 434 mg/m <sup>3</sup>	NZ OEL
		TWA	20 ppm	ACGIH
4,4'-methylenediphenyl diisocyanate	101-68-8	STEL	125 ppm	ACGIH
		WES-TWA	0.02 mg/m <sup>3</sup> (As -NCO)	NZ OEL
		Further information: Sensitiser, These values apply to all isocyanates, including prepolymers, present in the workplace air as vapours, mist or dust.		
		WES-STEL	0.07 mg/m <sup>3</sup> (As -NCO)	NZ OEL
		Further information: Sensitiser, These values apply to all isocyanates, including prepolymers, present in the workplace air as vapours, mist or dust.		
		TWA	0.005 ppm	ACGIH

#### Personal protective equipment

- Respiratory protection : Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines. The filter class for the respirator must be suitable for the maximum expected contaminant concentration (gas/vapour/aerosol/particulates) that may arise when handling the product. If this concentration is exceeded, self-contained breathing apparatus must be used.
- Hand protection : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.

# SAFETY DATA SHEET

## SikaBond® T55



Version 1.0

MSDS Number: 000000601639

Revision Date: 2015/12/08

- Eye protection : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary.
- Skin and body protection : Choose body protection in relation to its type, to the concentration and amount of dangerous substances, and to the specific work-place.

---

### SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

- Appearance : paste
- Colour : light brown
- Odour : ester-like
- Odour Threshold : No data available
- pH : No data available
- Melting point/range / Freezing point : No data available
- Boiling point/boiling range : No data available
- Flash point : ca. 38 °C (100 °F)  
Method: closed cup
- Evaporation rate : No data available
- Flammability : No data available
- Upper explosion limit : No data available
- Lower explosion limit : No data available
- Vapour pressure : No data available
- Relative vapour density : No data available
- Density : ca. 1.37 g/cm<sup>3</sup> (23 °C (73 °F) ())
- Solubility(ies)  
Water solubility : insoluble
- Partition coefficient: n-octanol/water : No data available
- Auto-ignition temperature : No data available
- Decomposition temperature : No data available
- Viscosity  
Viscosity, dynamic : No data available

# SAFETY DATA SHEET

## SikaBond® T55



Version 1.0

MSDS Number: 000000601639

Revision Date: 2015/12/08

Viscosity, kinematic : > 7 mm<sup>2</sup>/s (40 °C)  
Molecular weight : No data available

---

### SECTION 10. STABILITY AND REACTIVITY

Reactivity : No dangerous reaction known under conditions of normal use.  
Chemical stability : The product is chemically stable.  
Possibility of hazardous reactions : Stable under recommended storage conditions.  
Vapours may form explosive mixture with air.  
Conditions to avoid : Heat, flames and sparks.  
Incompatible materials : No data available

---

### SECTION 11. TOXICOLOGICAL INFORMATION

#### Acute toxicity

Not classified based on available information.

#### Components:

##### **aromatic polyisocyanate:**

Acute oral toxicity : LD50 Oral (Rat): > 5,000 mg/kg

##### **4,4'-methylenediphenyl diisocyanate:**

Acute inhalation toxicity : Acute toxicity estimate: 1.5 mg/l  
Test atmosphere: dust/mist  
Method: Expert judgement

#### **Skin corrosion/irritation**

Causes mild skin irritation.

#### **Serious eye damage/eye irritation**

Causes serious eye irritation.

#### **Respiratory or skin sensitisation**

Skin sensitisation: May cause an allergic skin reaction.

Respiratory sensitisation: May cause allergy or asthma symptoms or breathing difficulties if inhaled.

#### **Chronic toxicity**

##### **Germ cell mutagenicity**

Not classified based on available information.

##### **Carcinogenicity**

Suspected of causing cancer.

##### **Reproductive toxicity**

Suspected of damaging fertility or the unborn child.

# SAFETY DATA SHEET

## SikaBond® T55



Version 1.0

MSDS Number: 000000601639

Revision Date: 2015/12/08

### **STOT - single exposure**

May cause damage to organs if swallowed.  
May cause damage to organs if inhaled.

### **STOT - repeated exposure**

Not classified based on available information.

### **Aspiration toxicity**

Not classified based on available information.

---

## SECTION 12. ECOLOGICAL INFORMATION

### **Ecotoxicity**

No data available

### **Persistence and degradability**

No data available

### **Bioaccumulative potential**

No data available

### **Mobility in soil**

No data available

### **Other adverse effects**

### **Product:**

Additional ecological information : There is no data available for this product.

---

## SECTION 13. DISPOSAL CONSIDERATIONS

### **Disposal methods**

Waste from residues : Do not contaminate ponds, waterways or ditches with chemical or used container.  
Send to a licensed waste management company.

Contaminated packaging : Empty remaining contents.  
Dispose of as unused product.  
Do not re-use empty containers.  
Do not burn, or use a cutting torch on, the empty drum.

---

## SECTION 14. TRANSPORT INFORMATION

### **International Regulation**

#### **IATA-DGR**

Not dangerous goods

#### **IMDG-Code**

Not dangerous goods

### **Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code**

Not applicable for product as supplied.

### **National Regulations**



# SAFETY DATA SHEET

## SikaBond® T55



Version 1.0

MSDS Number: 000000601639

Revision Date: 2015/12/08

---

**NZS 5433**

Not dangerous goods

---

**SECTION 15. REGULATORY INFORMATION****Safety, health and environmental regulations/legislation specific for the substance or mixture**

International Chemical Weapons Convention (CWC) : Not applicable  
Schedules of Toxic Chemicals and Precursors

**HSNO Approval Number**

HSR002669

**HSNO Controls**

Approved handler certificate required  
HSNO tracking not required.  
Refer to EPA user guide to the HSNO control regulations for further information.

**The components of this product are reported in the following inventories:**

NZIoC : Not in compliance with the inventory

---

**SECTION 16. OTHER INFORMATION**

Date format : dd.mm.yyyy

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.