



3M[™] High Performance Green Masking Tape 401+

3M[™] High Performance Green Masking Tape 401+ is the preferred choice among industrial painters who demand results. Built on a foundation of innovation, 401+ tape is designed to deliver super-sharp paint lines in applications where surface temperatures can reach up to 250°F. When you consider 401+ can also be used to accomplish everything 3M[™] Industrial Masking Tapes 101+, 201+ and 301+ can do, it's quite possibly the most versatile tape in the line. It's one mean, green, masking machine, designed to deliver the consistently superior results you've come to expect from 3M.

Product Highlights

- Superior adhesion to metal, rubber, glass and plastic, while removing cleanly in one piece with no adhesive residue
- Highly conformable to many surfaces
- Resists paint bleed-through and creates super-sharp paint lines
- Green backing improves visibility and accuracy during paint masking
- Ideal for high performance industrial painting, including twotone color applications on trucks, buses, trailers, trains, fire trucks, ambulances and airplanes
- Withstands surface temperatures up to 250°F (121°C) for 30 minutes

3M™ High Performance Green Masking Tape 401+

Tape Size	UPC	Roll/Case
Bulk		
6 mm x 55 m	00-051115-69109-6	96
12 mm x 55 m	00-051115-64759-8	48
18 mm x 55 m	00-051115-64760-4	48
24 mm x 55 m	00-051115-64761-1	24
36 mm x 55 m	00-051115-64762-8	16
48 mm x 55 m	00-051115-64763-5	12
72 mm x 55 m	00-051115-64764-2	8
96 mm x 55 m	00-051115-64765-9	8
1490 mm x 55 m	00-051115-64766-6	1
Individually wrapped		
24 mm x 55 m	00-051115-64767-3	24
36 mm x 55 m	00-051115-64768-0	16
48 mm x 55 m	00-051115-64769-7	12



Industrial Adhesives and Tapes Division

Building 225-3S-06 St. Paul, MN 55144-1000 1-800-362-3550 www.3M.com/MaskingMadeSimple www.3M.com/industrialtapes 3M is a trademark of 3M Company.
Scotch is a registered trademark of 3M Company.
Please recycle. Printed in USA.
© 3M 2013. All rights reserved.
70-0716-1647-1 Rev. A



Conforms to irregular surfaces



Removes cleanly



Ideal for two-tone color applications



Consistently superior finishes

PRODUCT USE: All statements, technical information and recommendations contained in this document are based upon tests or experience that 3M believes are reliable. However, many factors beyond 3M's control can affect the use and performance of a 3M product in a particular application, including the conditions under which the product is used and the time and environmental conditions in which the product is expected to perform. Since these factors are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for the user's method of application. WARRANTY AND LIMITED REMEDY: Unless stated otherwise in 3M's product literature, packaging inserts or product packaging for individual products, 3M warrants that each 3M product meets the applicable specifications at the time 3M ships the product. Individual products may have additional or different warranties as stated on product literature, package inserts or product packages. 3M MAKES NO OTHER WARRANTIES, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR ANY IMPLIED WARRANTY ARISING OUT OF A COURSE OF DEALING, CUSTOM OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's application. If the 3M product is defective within the warranty period, your exclusive remedy and 3M's and seller's sole obligation will be, at 3M's option, to replace the product or refund the purchase price. LIMITATION OF LIABILITY: Except where prohibited by law, 3M and seller will not be liable for any loss or damage arising from the 3M product, whether direct, indirect, special, incidental or consequential, regardless of the legal theory asserted, including warranty, contract, negligence or strict liability.



Learn more about 3M[™] Industrial Masking Tapes at 3M.com/MaskingMadeSimple or call 1-800-362-3550.