

PROBOND E-317

TECHNICAL DATA SHEET

PROBOND E-317 EVA Adhesive

Low viscosity EVA adhesive for a variety of applications and substrates.

Common uses include paper lamination, core winding, textile and fabric lamination and general craft use.

Suitable for most paper stocks, cardboard, fabrics, polystyrene, wood etc.

Cured adhesive complies with FDA Regulation article 21FR175.105 for indirect contact with foodstuffs.



TECHNICAL DETAILS

Raw Material Base	EVA
Appearance	White Liquid
Viscosity	3,500 cps
Coverage	6-8mtr per ltr
Solids	36%
Odour	Slight PVA
Clean up	Water while wet
Sizes	500ml, 5ltr, 10ltr, 20kg, 210kg
Shelf Life	1 year in a cool dry place

USES

- Case & Carton Sealing
- Pattern Making
- Furniture & Upholstery
- Packaging & Displays

FEATURES

- Fast setting
- Fridge & freezer grade
- Low VOC & low odour
- · Arts & Crafts

APPLICATION

All surfaces to be glued must be clean and dry. Remove all oil, grease, wax, old glue, finish or other foreign material before gluing.

For best results, temperatures should be above 15°C for both the work area and the stock being used. Application from Glue Guru Pro-Bottles is the easiest and recommended method. Product can also be poured from larger vessels and spread with appropriate plastic spreaders, brushes or rollers.

Join surfaces as soon as possible within 7 minutes.

After use, the brushes, glue baths or other equipment should be washed with water.

Not recommended for high strength wood to wood applications due to its flexible glue line.

STORAGE & HANDLING

Store PROBOND E-317 on a wooden pallet in a cool place between 5°C to 30°C.

Keep out of direct sunlight and protect from freezing. Always test the suitability of the product for your application before use.

Refer to the Material Safety Data Sheet for further information.



