

1. Unique identification code of the product-type:

Quilosa MS INSTANT



2. **Type, batch or serial number** or any other element allowing identification of the construction product as required pursuant to Article 11(4): batch number: see packaging of the product
3. **Intended use or uses** of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer: **EN 15651-1:2012 Type F-INT** (only for interior use) non-structural sealants for joints only on the internal side of facade elements
4. Name, registered trade name or registered trade mark and contact address of the **manufacturer** as required pursuant to Article 11(5): Selena Iberia S.L.U.
Marie Curie, 19 - Planta 6.1
28521 RIVAS Madrid
Spain
5. Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2): Selena Iberia S.L.U. Marie Curie, 19 - Planta 6.1 28521 RIVAS Madrid
6. **System or systems of assessment** and verification of constancy of performance of the construction product as set out in Annex V: system 4 for type of testing
system 4 for the reaction to fire
7. In case of the declaration of performance concerning a construction product covered by a **harmonised standard**: not relevant
8. In case of the declaration of performance concerning a construction product for which a **European Technical Assessment** has been issued: not relevant
9. Declared performance

EN 15651-1:2012 Type F-INT
Conditioning: Method A
Substrate: glass without primer

Essential characteristics	Performance	Test Standard	Harmonised technical specification
Reaction to fire	Class F	EN 13501-1:2007+A1	EN 15651-1:2012
Release of chemicals dangerous to the environment and health	See product safety data sheet	EN 15651-1:2012; 4.5	EN 15651-1:2012
Water tightness and air tightness:			
Resistance to flow	≤ 5 mm	modified EN ISO 7390	EN 15651-1:2012
Loss of volume	≤ 45 %	EN ISO 10563	EN 15651-1:2012

Tensile properties: Elongation at break at 23 °C	≥ 25 %	EN ISO 8339	EN 15651-1:2012
Durability	Pass	EN ISO 8340, EN ISO 9047, EN ISO 10590	EN 15651-1:2012

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9.

Signed for and on behalf of the manufacturer by:

Lorenzo Garrido García
(Technical Manager)



17.03.2014, Madrid

Anex

According to Art. 6 (5) of the Regulation (EU) No. 305/2011 a Safety Data sheet according Regulation (EU) No. 1907/2006 (REACH), Annex II is annexed to this Declaration of Performance