Sika Boom & Sika Boom-G



Version 1.0 MSDS Number: 000000117321 Revision Date: 2015/12/01

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Product name : Sika Boom and Sika Boom-G

Product code : 000000117321

Type of product : aerosol

Recommended use of the chemical and restrictions on use

Product use : Polyurethane foam

Manufacturer or supplier's details

Company : Sika (NZ) Ltd.

85-91 Patiki Road

Avondale

Auckland AKL 1026

Telephone : +64 9 820 2900

Emergency telephone num-

ber

: 0800 734 607

Telefax : +64 9 828 4091

E-mail address : info@nz.sika.com

SECTION 2. HAZARDS IDENTIFICATION

GHS Classification

Flammable aerosols : Category A

Acute toxicity (Inhalation) : Category E

Skin irritation : Category B

Eye irritation : Category A

Specific Target Organ Toxicity

(Inhalation)

: Category A

Aquatic toxicity (Acute or

Chronic)

: Category D

GHS Label element

Hazard pictograms








Signal word : Danger

Hazard statements : H223 Flammable aerosol.

Sika Boom & Sika Boom-G



H316 Causes mild skin irritation. H319 Causes serious eye irritation. H333 May be harmful if inhaled.

H370 Causes damage to organs if inhaled.

H402 Harmful to aquatic life.

Precautionary statements

: P101 If medical advice is needed, have product container or

label at hand.

P102 Keep out of reach of children.

P103 Read label before use.

Prevention:

P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.

P211 Do not spray on an open flame or other ignition source. P251 Pressurized container: Do not pierce or burn, even after use

P260 Do not breathe dust/ fume/ gas/ mist/ vapours/ spray.

P264 Wash skin thoroughly after handling.

P270 Do not eat, drink or smoke when using this product.

P273 Avoid release to the environment.

P280 Wear protective gloves/ eye protection/ face protection.

Response:

P304 + P312 IF INHALED: Call a POISON CENTER or doctor/physician if you feel unwell.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P307 + P311 IF exposed: Call a POISON CENTER or doctor/physician.

P321 Specific treatment (see supplemental first aid instructions on this label).

P332 + P313 If skin irritation occurs: Get medical advice/ attention

P337 + P313 If eye irritation persists: Get medical advice/ attention.

Storage:

P405 Store locked up.

P410 + P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F.

Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

Other hazards which do not result in classification

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Hazardous components

Chemical Name	CAS-No.	Concentration (%)
Diphenylmethanediisocyanate, isomeres and	9016-87-9	>= 10 - < 20
homologues		
dimethyl ether	115-10-6	>= 1 - < 10

2/9

Sika Boom & Sika Boom-G

Version 1.0 MSDS Number: 000000117321 Revision Date: 2015/12/01

isobutane	75-28-5	>= 1 - < 10
propane	74-98-6	>= 1 - < 10
tris(2-chloro-1-methylethyl) phosphate	13674-84-5	>= 1 - < 10

SECTION 4. FIRST AID MEASURES

General advice : Move out of dangerous area.

Consult a physician.

Show this safety data sheet to the doctor in attendance.

If inhaled : Move to fresh air.

In case of skin contact : Take off contaminated clothing and shoes immediately.

Wash off with soap and plenty of water. If symptoms persist, call a physician.

In case of eye contact : Immediately flush eye(s) with plenty of water.

Remove contact lenses.

Keep eye wide open while rinsing.

If eye irritation persists, consult a specialist.

If swallowed : Clean mouth with water and drink afterwards plenty of water.

Induce vomiting immediately and call a physician.

Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

Most important symptoms and effects, both acute and

delayed

: irritant effects sensitising effects

Asthmatic appearance Allergic reactions Excessive lachrymation

Dermatitis

See Section 11 for more detailed information on health effects

and symptoms.

Causes mild skin irritation. Causes serious eye irritation. May be harmful if inhaled.

Causes damage to organs if inhaled.

Notes to physician : Treat symptomatically.

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media : Use extinguishing measures that are appropriate to local cir-

cumstances and the surrounding environment.

Unsuitable extinguishing

media

: Water

Hazardous combustion prod-

ucts

: No hazardous combustion products are known

Specific extinguishing meth-

ods

: Use water spray to cool unopened containers.

Sika Boom & Sika Boom-G



MSDS Number: 000000117321 Revision Date: 2015/12/01 Version 1.0

Special protective equipment

for firefighters

: In the event of fire, wear self-contained breathing apparatus.

SECTION 6. ACCIDENTAL RELEASE MEASURES

tive equipment and emer-

gency procedures

Personal precautions, protec- : Use personal protective equipment. Deny access to unprotected persons.

Environmental precautions : Do not flush into surface water or sanitary sewer system.

If the product contaminates rivers and lakes or drains inform

respective authorities.

Methods and materials for containment and cleaning up : Allow to solidify, use mechanical handling equipment.

SECTION 7. HANDLING AND STORAGE

Advice on protection against

fire and explosion

: Keep away from heat/sparks/open flames/hot surfaces. No smoking. Do not spray on a naked flame or any incandescent material. Take precautionary measures against electrostatic

discharges.

Advice on safe handling : Avoid exceeding the given occupational exposure limits (see

section 8).

Do not get in eyes, on skin, or on clothing. For personal protection see section 8.

Persons with a history of skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being

used.

Smoking, eating and drinking should be prohibited in the ap-

plication area.

Take precautionary measures against static discharge. Open drum carefully as content may be under pressure. Follow standard hygiene measures when handling chemical

products

Hygiene measures Handle in accordance with good industrial hygiene and safety

practice.

When using do not eat or drink. When using do not smoke.

Wash hands before breaks and at the end of workday.

Conditions for safe storage : BEWARE: Aerosol is pressurized. Keep away from direct sun

exposure and temperatures over 50 °C. Do not open by force or throw into fire even after use. Do not spray on flames or

red-hot objects.

Store in original container.

Keep container tightly closed in a dry and well-ventilated

place.

Observe label precautions.

Store in accordance with local regulations.

Sika Boom & Sika Boom-G



Version 1.0 MSDS Number: 000000117321 Revision Date: 2015/12/01

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis	
Diphenylmethanediisocyanate, isomeres and homologues	9016-87-9	WES-TWA	0.02 mg/m3 (As -NCO)	NZ OEL	
	Further information: Sensitiser, These values apply to all isocyanates, including prepolymers, present in the workplace air as vapours, mist or dust.				
		WES-STEL	0.07 mg/m3 (As -NCO)	NZ OEL	
	Further information: Sensitiser, These values apply to all isocyanates, including prepolymers, present in the workplace air as vapours, mist or dust.				
dimethyl ether	115-10-6	WES-TWA	400 ppm 766 mg/m3	NZ OEL	
		WES-STEL	500 ppm 958 mg/m3	NZ OEL	
isobutane	75-28-5	TWA	1,000 ppm	ACGIH	
		STEL	1,000 ppm	ACGIH	
propane	74-98-6	TWA	1,000 ppm	ACGIH	

Personal protective equipment

Respiratory protection : Use respiratory protection unless adequate local exhaust

ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines. The filter class for the respirator must be suitable for the max-

imum expected contaminant concentration

(gas/vapour/aerosol/particulates) that may arise when handling the product. If this concentration is exceeded, self-

contained breathing apparatus must be used.

Hand protection : Chemical-resistant, impervious gloves complying with an ap-

proved standard should be worn at all times when handling chemical products if a risk assessment indicates this is nec-

essary.

Eye protection : Safety eyewear complying with an approved standard should

be used when a risk assessment indicates this is necessary.

Skin and body protection : Choose body protection in relation to its type, to the concen-

tration and amount of dangerous substances, and to the spe-

cific work-place.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : liquid

Colour : various

Odour : characteristic

Sika Boom & Sika Boom-G

Version 1.0 MSDS Number: 000000117321 Revision Date: 2015/12/01

Odour Threshold : No data available

pH : Not applicable

Melting point/range / Freezing

point

: No data available

Boiling point/boiling range : No data available

Flash point : Not applicable

Evaporation rate : No data available

Flammability (solid, gas) : No data available

Upper explosion limit : Upper flammability limit

26.2 %(V)

Lower explosion limit : lower flammability limit

1.5 %(V)

Vapour pressure : 5,500 - 6,000 hPa (4,125 - 4,500 mmHg)

Relative vapour density : No data available

Density : ca. 1 g/cm3 (20 °C (68 °F) ())

Solubility(ies)

Water solubility : insoluble

Partition coefficient: n-

octanol/water

: No data available

Auto-ignition temperature : > 230 °C (> 446 °F)

Decomposition temperature : No data available

Viscosity

Viscosity, dynamic : Not applicable

Viscosity, kinematic : Not applicable

Molecular weight : No data available

SECTION 10. STABILITY AND REACTIVITY

Reactivity : No dangerous reaction known under conditions of normal use.

Chemical stability : The product is chemically stable.

Possibility of hazardous reac-

tions

: Stable under recommended storage conditions.

Conditions to avoid : Heat, flames and sparks.

Sika Boom & Sika Boom-G

Version 1.0 MSDS Number: 000000117321 Revision Date: 2015/12/01

Incompatible materials : No data available

SECTION 11. TOXICOLOGICAL INFORMATION

Acute toxicity

May be harmful if inhaled.

Components:

Diphenylmethanediisocyanate, isomeres and homologues:

Acute oral toxicity : LD50 Oral (Rat): > 10,000 mg/kg

Acute inhalation toxicity : Acute toxicity estimate: 1.5 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist Method: Expert judgement

Acute dermal toxicity : LD50 Dermal (Rabbit): > 9,400 mg/kg

Skin corrosion/irritation

Causes mild skin irritation.

Serious eye damage/eye irritation

Causes serious eye irritation.

Respiratory or skin sensitisation

Skin sensitisation: Not classified based on available information.

Respiratory sensitisation: Not classified based on available information.

Chronic toxicity

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Not classified based on available information.

Reproductive toxicity

Not classified based on available information.

STOT - single exposure

Causes damage to organs if inhaled.

STOT - repeated exposure

Not classified based on available information.

Aspiration toxicity

Not classified based on available information.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

No data available

Sika Boom & Sika Boom-G



Version 1.0 MSDS Number: 000000117321 Revision Date: 2015/12/01

Persistence and degradability

No data available

Bioaccumulative potential

No data available

Mobility in soil

No data available

Other adverse effects

Product:

Additional ecological infor-

mation

: There is no data available for this product.

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : Do not contaminate ponds, waterways or ditches with chemi-

cal or used container.

Send to a licensed waste management company.

Contaminated packaging : Empty remaining contents.

Dispose of as unused product. Do not re-use empty containers.

Do not burn, or use a cutting torch on, the empty drum.

SECTION 14. TRANSPORT INFORMATION

International Regulation

IATA-DGR

UN/ID No. : UN 1950

Proper shipping name : Aerosols, flammable

Class : 2.1

Packing group : Not assigned by regulation

Labels : 2.1 Packing instruction (cargo : 203

aircraft)

Packing instruction (passen-

: 203

ger aircraft)

IMDG-Code

UN number : UN 1950 Proper shipping name : AEROSOLS

Class : 2.1

Packing group : Not assigned by regulation

Labels : 2.1 EmS Code : F-D, S-U Marine pollutant : no

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

Sika Boom & Sika Boom-G



Version 1.0 MSDS Number: 000000117321 Revision Date: 2015/12/01

National Regulations

NZS 5433

UN number : UN 1950
Proper shipping name : AEROSOLS

Class : 2.1

Packing group : Not assigned by regulation

Labels : 2.1

SECTION 15. REGULATORY INFORMATION

Safety, health and environmental regulations/legislation specific for the substance or mix-

Special labelling of certain

mixtures

: Persons already sensitised to diisocyanates may develop

allergic reactions when using this product.

Persons suffering from asthma, eczema or skin problems should avoid contact, including dermal contact, with this prod-

uct.

This product should not be used under conditions of poor ventilation unless a protective mask with an appropriate gas filter

(i.e. type A1 according to standard EN 14387) is used.

International Chemical Weapons Convention (CWC) : Not applicable

Schedules of Toxic Chemicals and Precursors

HSNO Approval Number

HSR002515

HSNO Controls

HSNO tracking not required.

Approved handler certificate not required.

The components of this product are reported in the following inventories:

NZIoC : On the inventory, or in compliance with the inventory

SECTION 16. OTHER INFORMATION

Date format : dd.mm.yyyy

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.