

# SuperGrip<sup>®</sup> 2 Hour

## Premium polyurethane construction adhesive

Construction

### Positioning

#### Description

A transparent polyurethane paste adhesive. SuperGrip 2 Hour is a versatile, ready to use general purpose construction adhesive.

#### Use

Bonding of:

- Particle board flooring
- Timber & MDF
- Marble & stone
- Concrete
- Brick/blocks
- Glass
- Fibre cement
- Tiles
- Rubber
- Metals
- Aluminium

#### Advantages

- 100% waterproof (BS-EN204)
- Incredibly strong
- Bonds almost anything, including LOSP treated timber
- Non drip
- No shrinkage
- Cures in 2 hours\*
- Interior and exterior use
- High temperature resistance (minus 30°C to +100°C)
- Cures transparent
- Does not stain

### Product Data

#### Form:

Transparent polyurethane paste

#### Colour:

Translucent

#### Storage/Shelf Life:

Twelve (12) months from date of production when stored in original, unopened packaging in cool, dry conditions.

#### Packaging:

310 ml cartridges

### Technical Data

#### Density:

1.12 g/cm<sup>3</sup>

#### Solids content:

100% approximately

#### Cure type:

Humidity curing

#### Application temperature:

5°C to 35°C

#### Service temperature:

-30°C to +100°C

#### Relocation time:

Approximately 30 minutes depending on temperature and ventilation.

#### \*Cure time:

Approximately 2 hours, depending on temperature, moisture content of surfaces and adhesive thickness. Strength will increase over the next 24 hours.

#### Flammability:

Non flammable

### Application Conditions

#### Surface Preparation

All surfaces must be clean and free from all dust, laitance, scale, rust, loose particles, grease and foreign matter.

#### Gun Application

- Cut end off cartridge nozzle at a 45° angle to give a 5-6 mm bead. Fit cartridge into a Sika gun.
- Apply adhesive thinly to one surface, or both surfaces if very porous or absorbent.
- Join surfaces within 30 minutes. A perfect fit is required for a watertight bond. Clamping or pressing will increase bond strength.
- Clamp time: 1-2 hours at 15°C to 20°C. Clamp for longer if the temperature is below 10°C.



<b>Cleaning</b>	<ul style="list-style-type: none"> <li>• Clean up with acetone or white spirit.</li> <li>• Cured adhesive can only be removed mechanically.</li> </ul>
<b>Important Notes</b>	
<b>Limitations</b>	<ul style="list-style-type: none"> <li>• One or both of the materials to be bonded must be porous.</li> <li>• Gap filling capacity is limited.</li> <li>• A perfect fit of components is required for a watertight bond.</li> <li>• Gap-filling and cure speed performance may be enhanced by a slight moistening of the substrate surfaces.</li> <li>• Surfaces may be damp or slightly moist, but all free liquid water must be removed.</li> </ul>
<b>Notes</b>	All technical data stated in this Product Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.
<b>Local Restrictions</b>	Please note that as a result of specific local regulations the performance of this product may vary from country to country. Please consult the local Product Data Sheet for the exact description of the application fields.
<b>Health &amp; Safety Instructions</b>	
<b>Protective Measures</b>	<ul style="list-style-type: none"> <li>• To avoid rare allergic reactions, we recommend the use of protective gloves. Change soiled work clothes and wash hands before breaks and after finishing work.</li> <li>• Local regulations as well as health and safety advice on packaging labels must be observed.</li> <li>• For further information refer to the Sika Material Safety Data Sheet which is available on request.</li> <li>• If in doubt always follow the directions given on the pack or label.</li> </ul>
<b>Important Notes</b>	<ul style="list-style-type: none"> <li>• Residues of material must be removed according to local regulations. Fully cured material can be disposed of as household waste under agreement with the responsible local authorities.</li> <li>• Detailed health and safety information as well as detailed precautionary measures e.g. physical, toxicological and ecological data can be obtained from the safety data sheet.</li> </ul>
<b>Legal Notes</b>	The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

