

WOODLOK GLAZE-AWAY Solvent Cleaner

WOODLOK Glazeaway is the original solvent based surface cleaner formulated to remove hot-melt residue, contact adhesive and handling marks.

WOODLOK GLAZEAWAY is safe on PVC edges as well HPL laminates, Melamine® and Melteca®.

Fast drying solvent.

Not suitable for ABS (see WOODLOK DSOLVAWAY)



PHYSICAL & CHEMICAL PROPERTIES :

Solvent :	Solvent Blend
Appearance :	Clear Liquid
Viscosity:	140cps
Flash Point :	24°C
Sizes:	4ltr Tin with pourer spout 20ltr Jerry Container

APPLICATION :

WOODLOK GLAZEAWAY is a strong solvent so always use in accordance with the products MSD Sheet.

CLEANING :

Either apply to a clean, dry cloth. And wipe or spray surface generously using the WOODLOK Spritzer Bottles and wipe.

HANDLING & STORAGE :

Keep lids on the containers when not in use to avoid solvent evaporation.
Product should be stored between 5°C and 25°C on a wooden pallet and kept from freezing.
Keep out of direct sunlight and away from sources of heat.

WARNINGS :

This industrial product is applied by mechanical methods.
Skin contact and breathing vapours, mists, or aerosols should be avoided. Use with adequate ventilation where vapour cannot accumulate in dangerous concentrations.
Empty containers can still be hazardous.
Keep well away from open fires, flames, gas and electrical equipment which is not flame proofed.

FIRST AID INSTRUCTIONS

SWALLOWED:

DO NOT induce vomiting.
Give 1 – 2 glasses of water and seek medical assistance.
Should the patient vomit, maintain a clear airway until medical assistance is obtained.

EYES:

Flush with water for 15 minutes.
It is advisable to obtain medical advice concerning an eye.

SKIN:

Wet down with water before removing clothing due to possibility of static discharge igniting vapour.
Wash affected areas thoroughly air dry outside then launder before re-use.

INHALATION:

Carefully remove persons to fresh air, avoid becoming affected yourself.
If patient is severely affected, seek medical assistance.
If the person stops breathing, apply artificial respiration and other first aid techniques until medical assistance arrives.

See MSDS for further specifics relating to this product.

TRANSPORT

PROPER SHIPPING NAME:	Flammable Liquid contains Ethyl Alcohol
UN No :	1993
Hazchem :	3[Y]E
Hazard Class :	3
Packing group :	II

INDUSTRIAL GRADE ADHESIVES FOR THE PROFESSIONAL

WOODLOK™

WOODLOK GLAZE-AWAY Solvent Cleaner

DISPOSAL :

When the container is empty, remove the lid and allow any adhesive residue to dry.

Dried residue and container can be disposed of in normal rubbish.

SHELF LIFE:

Best used within 9 months from date of manufacture when stored under the above conditions in the original unopened containers.

WOODLOK PRODUCT RANGE

There are other adhesives within the WOODLOK range. These all have different attributes and need to be selected according to your requirements.

WOODLOK 2200 Aliphatic Resin

Cost effective Aliphatic with long open time of up to 15 minutes. Excellent for laminating full sheets of MDF and Particleboard. General purpose

WOODLOK 2300 Premium Aliphatic Resin

High strength, fast setting Aliphatic for general use. Excellent all-rounder and our most popular WOODLOK aliphatic resin.

WOODLOK 2400 Hardline Aliphatic Resin

High strength, fast setting Aliphatic which dries to a hard glue line. Best sandability.

WOODLOK 2500 D3 Crosslinking Adhesive

Water resistant (D3) crosslinking adhesive cures to form a tough, heat resistant (100°C) bond. Excellent all-round to interior and exterior use. Used for bonding HPL laminate to MDF or particleboard.

WOODLOK 2550 D3 Crosslinking High Viscosity

Higher viscosity (thicker) version of the WOODLOK 2500 Crosslink. Longer open time.

WOODLOK 3150 Melamine Adhesive (NEW)

Ready to use, single pack adhesive formulated for bonding synthetic laminated panels (Melamine) to MDF, particleboard and other porous substrates. Easy to apply and dries clear.

WOODLOK 3010 - 10min / 3030 - 30min / 3090 - 90min

Next generation thixotropic gel polyurethane construction adhesive. Waterproof. Ready to use, single part adhesive uses the latest technology to deliver extreme bond strength and hard glue lines. Easy to dispense 300ml standard cartridges in three cure speeds.

WOODLOK 3500 - 4hour / 3600 - 30min

Moisture cure interior / exterior liquid polyurethane adhesive. Waterproof and resistant to heat and chemicals. Bonds virtually any surface like metals, stainless steel, wood, stone, glass, most plastics and other difficult surfaces.

WOODLOK 8000 Marine Grade Structural Epoxy

Easy mix 1:1 thixotropic epoxy for bonding wood, concrete, fibreglass, stone and marble, metals and some plastics

WOODLOK GLAZEAWAY Solvent Cleaner

Solvent for final cleaning PVC edges and counter tops.

WOODLOK DSOLVAVAY Citrus Cleaner

Citrus cleaner for final cleaning PVC and ABS Edges and tops. Low odour, high performance surface cleaner.

